


Data Sheet

Type Number 30395
Designation IEC SR 57
System Silver oxide / Zinc /
 KOH - Electrolyte



Nominal Voltage 1,55 V
Typical Capacity C 48 mAh
 Load 13 kOhm, at 20°C down to 1.2 V

Weight (approx.) 0,75 g
Volume 0,17 ccm
Coding..... Date of Manufacturing
 Month / Year

| | | |
|---------------------------|-------|------|
| Temperature Ranges | min | max. |
| Storage | -10°C | 65°C |
| Discharge | -10°C | 65°C |

| | | |
|--------------------|------|------|
| Dimensions | min | max. |
| Diameter (Ø)..... | 9,15 | 9,5 |
| Height A/(B) | 2,4 | 2,7 |

Segment Watch

Typical Capacities (at 20°C)

| Discharge Type | Load | End Voltage: | 1.2 V |
|--------------------------|---------|-----------------|-------|
| Continuous 24h/d,7d/w | 13000 Ω | Time: | 400 h |
| | | Capacity [mAh]: | 48 |
| | | Energy [mWh]: | 74 |

All Data contained herein is for single cells

For battery applications, performance data may vary from single cell data, depending on specific battery configuration

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst
 Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Subject to change without prior notice!
 Date of issue: 2012-04-12