

Cellomur®

DESCRIPTION

Cellomur® is a rigid, straight-edged, fire-retardant expanded polystyrene insulation panel for external insulation **under thin plaster.**

With dimensions of **1200 mm x 600 mm**, they allow the walls to be insulated from the outside to provide better living comfort.

This panel complies with the **NF EN 13163** standard, **CPT3035V3**, the **technical notices** of the various ETICS system owners and is eligible for EEC for the BAR102 sheet.

PRODUCT CHARACTERISTICS

- **Destination**
External thermal insulation under plaster
- **Usage** Exterior walls
- **Thermal conductivity**
38, mW/m.K
- **ACERMI N°**
12/081/793
- **European Norm**
CE mark according to NF EN 13163
- **How to implement**
The implementation must comply with the Cahier des Prescriptions Techniques du CSTB n°3035-V3, with the regulations and with the Technical Notices of the ETICS System Holders:
 - doweled
 - gluedThe product is compatible with organic and hydraulic plasters.



THE + PRODUCTS

- Panel perfectly suited to thermal insulation from the outside under thin plaster.
- Excellent durability
- Lightweight and easy to cut



Energy saving



Preserved
Environnement



Light product



Certified recycling





Cellomur®

CONDITIONING

Name of the article	Cellomur® 130 60/120	Cellomur® 20 60/120	Cellomur® 30 60/120	Cellomur® 40 60/120
Sales packaging	Pack of 3 panels	Pack of 25 panels	Pack of 16 panels	Pack of 12 panels
Thermal resistance (m²-K/W)	3,40	0,50	0,75	1,05

Name of the article	Cellomur® 50 60/120	Cellomur® 60 60/120	Cellomur® 70 60/120	Cellomur® 80 60/120
Sales packaging	Pack of 10 panels	Pack of 8 panels	Pack of 7 panels	Pack of 6 panels
Thermal resistance (m²-K/W)	1,30	1,55	1,85	2,10

Name of the article	Cellomur® 90 60/120	Cellomur® 100 60/120	Cellomur® 110 60/120	Cellomur® 120 60/120
Sales packaging	Pack of 5 panels	Pack of 5 panels	Pack of 4 panels	Pack of 4 panels
Thermal resistance (m²-K/W)	2,35	2,60	2,90	3,15

Name of the article	Cellomur® 180 60/120	Cellomur® 190 60/120	Cellomur® 200 60/120	Cellomur® 140 60/120
Sales packaging	Pack of 3 panels	Pack of 2 panels	Pack of 2 panels	Pack of 3 panels
Thermal resistance (m²-K/W)	4,75	5,00	5,25	3,70

Name of the article	Cellomur® 150 60/120	Cellomur® 160 60/120	Cellomur® 170 60/120
Sales packaging	Pack of 3 panels	Pack of 3 panels	Pack of 3 panels
Thermal resistance (m²-K/W)	3,95	4,20	4,45

CU: consumer unit
Additional thicknesses can be offered on request



GOOD TO KNOW

PDF documentation

available online at www.hirschisolation.fr :
FDES, Declarative and regulatory sheets,
Product documentation, DOP, ACERMI,
Standard description

